

Heavy Duty Electric Rough Terrain Pallet Truck



They are used out on site where no ordinary pallet truck can go and/or forklifts are not allowed (e.g. rooftops). Thanks to the large wheels and straddle forks arrangement they can be used for any type of pallet up to approx. 1200 x 1200mm on uneven ground.

- Transports loads on uneven ground
- Strong & light tubular steel framing
- Little maintenance required
- Great manoeuvrability
- Hydraulic fork lift with inbuilt hand pump
- Adjustable width over forks
- Driving axle on self-lubricating bearings
- Wheels fitted onto sealed bearings
- Large pneumatic load wheels
- Easy handling
- Built-in charger
- 2 heavy duty batteries for full day operation

SPECIFICATIONS

CAPACITY (kg)	LOAD CENTRE (mm)	FORK LENGTH	WIDTH OVER FORKS (mm)	MAX PALLET SIZE (mm)	DRIVE WHEEL MOTOR (S)	BATTERY	STRADDLE GAP (mm)	MODEL
1200	500	890 mm	160 - 560	1200 x 1200	1 x 500 DC	2 x 60A	1250	TNE1200 1DC
1200	500	890 mm	160 - 560	1200 x 1200	1 x 1000 AC	2 x 100A	1250	TNE1200 1AC
1200	500	890 mm	160 – 560	1200 x 1200	2 x 500 DC	2 x 100A	1250	TNE1200 2DC
1500	500	1000 mm	160 - 900	1200 x 1200	1 x 2500 AC	2 x 100A	1266	TNE1500 AC

GRADABILITY

RAISED FORK HEIGHT (mm)	LOWERED FORK HEIGHT (mm)	MODEL
220 / 260	45	TNE1200 1DC
220 / 260	45	TNE1200 1AC
220 / 260	45	TNE1200 2DC
400	45	TNE1500 AC

GRADIENT	TNE1200 1DC	TNE1200 1AC	TNE1200 2DC	TNE1500 AC
0%	1200kg	1200kg	1200kg	1500kg
1%	1200kg	1200kg	1200kg	1500kg
3%	-	1200kg	1200kg	1500kg
4%	800kg	-	1200kg	1500kg
5%	-	-	1200kg	1500kg
6%	-	800kg	1200kg	1500kg
8%	-	-	1200kg	1500kg
10%	-	500kg	1200kg	1500kg
14%	300kg	-	-	1500kg
15%	-	-	800kg	1500kg
18%	-	300kg	-	1500kg
20%	0kg	-	-	-
23%		-	500kg	1200kg
25%		0kg	-	-
30%			300kg	800kg
40%			-	500kg
45%			0kg	-
50%				300kg
60%				0kg



TNE1200 2DC Model

