MGTP 45 SSF

Ready to Rent 45kVA Diesel Generator

When looking for robust, reliable, good quality 45kVA Universal Rental Solution, our MGTP 45 SSF has everything the hire market requires.



Optional extras:





45kVA 3ph Aux Power (400V)

Linz alternator

FPT (Iveco) diesel engine

Engine protection shutdown system

3 way fuel valve

12V battery isolator switch

Emergency stop button

Variable RCD

ELR bypass switch (activated by key only)

Fully bunded base (110%)

Engine oil drain pump

Features Benefits

Plenty of power to meet the demands of medium generator hire

Heavy duty and proven reliability

World class performance and watercooled

In the case of low fuel, low oil pressure, high engine temp and battery charge failure

Easy connectivity to an external fuel tank

Reduces flat battery breakdowns

A must on any UK site

Flexible protection

Turn off the ELR to avoid nusiance tripping when powering electrical motors

To retain all spilt fluids

Reducing service time



Specification

Performance

Alternator	Linz (AVR Controlled)			
Single Phase Power (11	10V) N/A			
Single Phase Power (23	30V) 15kVA/ 12kW			

Three Phase Power (400V)	45kVA/ 36kW		
Noise Level LWA=88	dBa@7m=63		
Insulation Class	Н		
Mechanical Protection - IP	23		

Engine

Make	FPT (Iveco)
Туре	N45 SM1F (Stage 3A)
Fuel	Diesel
Number of Cylinde	rs 4
Power (HP)	83
Engine Speed (RPA	M) 1500
Cooling	Water

Fuel Consumption @ 75% Load (Litres/hour)				
Fuel Tank Capacity (Litres)				
Average Runtime (Hours)				
@ 100% Load	22	@ 75% Load	31	
@ 50% Load	41	@ 25% Load	63	
Control Panel Deepsea 7310 c/w two wire Auto Start/ Stop facility				

Dimensions (Machine only)

Longth: 21/12 mm

Length: 2142 mm	Width: 10/0 mm			Height: 1750 mm			
Dry Weight (No Fuel): 1382 k	κg		Wet Weight (Fuel Full): 1682 kg				
Dimensions (With ro	ad-tow	kit)					
Length: TBA mm	Width: TBA mm			Height: TBA mm			
Dry Weight (No Fuel): TBA kg Wet Weight (Fuel Full): TBA kg							
Socket	3ph (400V)		<i>I</i>)	1ph (230V)	1ph (110V)	
Configuration	63A	32A	16A	32A	16A	32A	16A
MGTP 45 SSF	1	1	-	4	2	-	-
Hard wire facility	3ph (400V)			l. /2201	1/1	1ph (110V)	
nard wire facility	3ph	(400V)		ph (230)	V)	ıpn (ı	101)

Width: 1070 mm

Hoight: 1750 mm